



Materials List

Item	Part Name	Materials
1	Body	Cast Iron: ASTM A126CL B , DIN1691 GG25, EN 1561 EN-GJL-200; GB12226 HT200; Ductile Cast Iron: ASTM A536 65-45-12, DIN 1693 GGG40, EN1563 EN-GJS-400-15, GB12227 QT450-10; Stainless Steel: ASTM A351 CF8, CF8M; CF3, CF3M; Carbon Steel: ASTM A216 WCB
2	Stem	Zinc Plated Steel; Stainless Steel: ASTM A276 Type 316, Type 410, Type 420; ASTM A582 Type 416;
3	Taper Pin	Stainless Steel: ASTM A276 Type 304, Type 316; EN 1.4501;
4	Seat	NBR, EPDM, Neoprene, PTFE, Viton;
5	Disc	Ductile Cast Iron (Nickel plated): ASTM A536 65-45-12, DIN 1693 GGG40, EN1563 EN-GJS-400-15, GB12227 QT450-10; Stainless Steel: ASTM A351 CF8, CF8M; CF3, CF3M; EN 1.4408, 1.4469; 1.4501; AL-Bronze: ASTM B148 C95400;
6	O-Ring	NBR, EPDM, Neoprene, Viton;
7	Bushing	PTFE, Nylon, Lubricated Bronze;
8	Key	Carbon Steel

This buyer can select material as per materials list. The customer may mark the material and temperature used, Our company may select instead. When the medium and temperature is special, please consult with our company.


Seat Temperature Ratings

Material		NBR	Neoprene	EPDM	Hypalon	Viton	PTFE
Temperature Ratings	℃	-20~100	-40~100	-40~120	-32~135	-12~230	-50~200
	℉	-4~212	-40~212	-40~248	-25.6~275	10.4~446	-58~392

Seat materials are capable of withstanding lower temperatures without damage. However, the elastomer becomes hard and torques increase. Some flow media may further restrict the published temperature limits or significantly reduce seat life.



Series F101 Wafer Type Butterfly Valve



Dimensions List (mm)

Size		E									F/M											
mm	inch	A	B	C	D	ANSI 125/150	PN10	PN16	10K	ANSI 125/150	PN10	PN16	10K	H	J	I-K	L	T	S	W		
40	1½	70	145	32	12.7	98.4	110	110	105	16	18	18	19	65	50	4-7	33	27	9	10		
50	2	76	162	32	12.7	120.7	125	125	120	19	18	18	19	65	50	4-7	42	32	9	10		
65	2½	89	174	32	12.7	139.7	145	145	140	19	18	18	19	65	50	4-7	45	47	9	10		
80	3	95	181	32	12.7	152.4	160	160	150	19	18	18	19	65	50	4-7	45	65	9	10		
100	4	114	200	32	15.9	190.5	180	180	175	19	18	18	19	90	70	4-9.5	52	90	11	12		
125	5	127	213	32	19.1	215.9	210	210	210	22	18	18	23	90	70	4-9.5	54	111	14	14		
150	6	139	225	32	19.1	241.3	240	240	240	22	22	22	23	90	70	4-9.5	56	145	14	14		
200	8	177	260	38	22.2	298.5	295	295	290	22	22	22	23	125	102	4-11.5	60	193	17	17		
250	10	203	292	38	28.6	362	350	355	355	25	22	26	25	125	102	4-11.5	66	241	22	22		
300	12	242	337	38	31.8	431.8	400	410	400	25	22	26	25	125	102	4-11.5	77	292	22	24		
350	14	277	368	45	31.8	476.3	460	470	445	29	22	26	25	125	102	4-11.5	77	325	22	24		
400	16	308	400	51	33.3	539.8	515	525	510	29	26	30	27	210	165	4-22	86	380	27	27		
450	18	342	422	51	38.1	577.9	565	585	565	32	26	30	27	210	165	4-22	105	428	27	27		
500	20	374	479	64	41.3	635	620	650	620	32	26	33	27	210	165	4-22	130	474	27	32		
600	24	459	562	70	50.8	749.3	725	770	730	35	30	36	33	210	165	4-22	152	575	36	36		
700	28	520	624	72	55	—	840	840	840	—	30	36	33	300	254	8-18	165	674	—	—		
750	30	545	650	72	55	914.4	900	900	900	1½"-7	33	36	33	300	254	8-18	167	726	—	—		
800	32	575	672	72	55	—	950	950	950	—	33	39	M30	300	254	8-18	190	771	—	—		
900	36	635	768	77	75	1085.9	1050	1050	1050	1½"-6	M30	M36	M30	300	254	8-18	207	839	—	—		
1000	40	685	823	85	85	—	1160	1170	1160	—	M33	M39	M36	300	254	8-18	216	939	—	—		
1050	42	765	858	85	85	1257.3	—	—	—	1½"-6	—	—	—	300	254	8-18	256	997	—	—		
1200	48	839	940	150	92	1422.4	1380	1390	1380	1½"-6	M36	M45	M36	350	298	8-22	276	1125	—	—		

✧ Please contact manufacturer if you want more flange standards.